

ELECTRICAL CONTACT CLEANER



EL™ 2302



For use on Electrical Equipment



NSF® Registered; K2 Rated (Solvents for cleaning electronic instruments) (Reg# 115091)



Evaporation rate: Fast



Flammable



Will not harm plastic



KB Solvency Strength (higher value, stronger the solvent): 342



HMIS Hazard Rating
Health (2) • Flammability (4) • Reactivity (0)

- Alternative to Freon TF113®
- For use on non-energized equipment
- Safe on most plastics
- Leaves no residue



PRESERVE. PROTECT. PREVENT.™

Sprayon® EL™ 2302 Electrical Contact Cleaner is a quick dry, non-ozone depleting cleaner that removes dirt, oil, and grease from sensitive equipment and precision instruments without leaving any residue. This formula is safe on most plastics and is packaged with extension tube for hard to reach areas.

ELECTRICAL & ELECTRONIC

USES

- Printed circuits
- Cameras (movie, 35mm & digital)
- Electronic games (TV/Video)
- Precision instruments
- Coin counters & chutes
- Telephone switch gears
- Vacuum tube parts
- Relays & switches
- Meters & timing devices
- Typewriters & office machines
- Hydraulic & missile fuel systems
- Satellite communications & radar equipment
- Computer systems & memory devices
- X-ray equipment



EL2302

APPLICATION

Spray in wellventilated area. Sprays best at room temperature (70°F). Shake well before using. NOTE: Do not use on electrical equipment while in operation. Allow surface to dry completely before restart. May harm certain plastics, elastomers and air-dry painted surfaces. Test product on non-essential similar material prior to application.

PERFORMANCE

- EVAPORATION RATE: Fast
KB VALUE (Cleaning Power): 342
DIELECTRIC STRENGTH: N/A
PLASTIC SAFE: Yes
- NSF Registration Number 115091; K2 Rated
 - Alternative to Freon TF113®
 - For use on non-energized equipment
 - Safe on most plastics
 - Leaves no residue
 - Fast evaporating
 - Equipped with an extension tube for hard-to-reach areas

PACKAGING

STOCK #: S02302
UPC CODE: 0-75577-92302-1
FILL WT: 11 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PROPERTIES

APPEARANCE: Clear Volatile Liquid
ODOR: Mild Solvent Odor/Slight Alcohol
PROPELLANT: CO₂
WT./GAL.: 6.66
SPECIFIC GRAVITY: 0.80
H.A.P.S. (HAZARDOUS AIR POLLUTANTS): No
SARA 313 CHEMICALS: No
% VOC AEROSOL: 75%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: 9°F
HAZARD RATING: 2, 4, 0
SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA
SHEETS: sprayon.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-EL2302